

## UL Certification

<b>INFINO</b>	Grade	HN-3204
---------------	-------	---------

Component - Plastics

E115797

### Guide Information

#### LOTTE CHEMICAL CORPORATION

56 Gosan-ro, Uiwang-si Gyeonggi-do 437-711 KR

#### HN-3204(+)(M)(f1)

Polycarbonate (PC), glass reinforced "INFINO", furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	V-0	1	1	80	80	80
	2.5	5VA	1	1	80	80	80
	3.0	V-0	1	1	80	80	80

Comparative Tracking Index (CTI): 3

Dielectric Strength (kV/mm): 27

High-Voltage Arc Tracking Rate (HVTR): 4

Dimensional Stability (%): -

Inclined Plane Tracking (IPT) kV: -

Volume Resistivity (10<sup>8</sup> ohm-cm): 15

Surface Resistivity (10<sup>8</sup> ohm-cm):

High Volt, Low Current Arc Resis (D495): 7

(+) - May be replaced by one, two, or three numbers and/or letter(s)

(M) - IEC CTI Solution B: CTI 125M

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2011-09-08

Last Revised: 2012-03-05

© 2020 UL LLC



IEC and ISO Test Methods				
Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	1.5	V-0 (ALL)
			2.5	5VA (ALL)
			3.0	V-0 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	1.5	960
			3.0	960
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	1.5	825
			3.0	850
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	CTI175
		Material Group	-	IIIa
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-

<https://ia.ul.com/>